



LEADER Fan

WATER-DRIVEN MH260

A concentrated, powerful jet of air due to:

- high-strength propeller matched to the power of the motor
- double-layer aluminum/ABS thermoplastic red shroud
- metal grille

Positioning from 3 ft to 20 ft

in front of a door without loss of power for:

- more space to move about
- less noise inside the building

Automatic optimal +10° tilt when handle raised

Precise tilt adjustment

from $+10^{\circ}$ to $+20^{\circ}$ for optimization of direction of air stream up entrance steps

Protective frame with gray epoxy coating

Stable & easy to handle even on unstable ground due to large rear wheels

Integrated misting system

Characteristics

Characteristics			
Model	MH260		
Reference	I61.00.033		
Open air flow	46,980 CFM		
PPV air flow according to AMCA	-		
Weight (dry)	108 lbs		
Dimensions L x H x D	27.9 x 28.3 x 24.3 inch		
Propeller diameter	22.4 inch		
Engine	Water-driven motor in aluminum with cutoff and control valve. With pressure gage		
Engine power	9 HP		
Power supply	Water under pressure		
Engine comsumption	165 GPM @ 145 PSI		
Engine supply couplings	2" male for inlet and outlet		
Integrated misting system	Yes		
Noise level	92.8 dB at 10 ft		
Ventilation type	PPV blowing		
Application	Single door (e.g. house, small apartment block) and double door (e.g. tall apartment block, mid-size industrial unit)		
	מהם מסטטוב מסט (ב.צ. נמו מאמו נדופות טוספת, דוום-טבפ וווטטטנוומו טוווג)		

Optional accessories:

16.4 ft ventilation duct	160.20.153	Protective cover	160.20.097
High expansion foam adapter without coupling delivered with 114.8 ft of polyane plastic film duct (products with coupling: see p. 52)	160.20.116	-10° prop for negative tilt of fan	160.20.108

) Ventilation tactics in the catalogue or at www.LeaderNorthAmerica.com Freely downloadable interactive ventilation courses at www.leader.educexpert.com As part of our policy of constant research to improve our products, we reserve the right to modify our products' characteristics at any time without notice

02/19 - ZCL03.265.US.6



45