



NEW !

PORTABLE MONITOR

VECTOR 2

1250 GPM Portable grounds monitor With safety valve

- Vector monitor consists of a turret and a base.
- Flow up to 1250 GPM
- **Base**, with **safety shut off** in case of movement, is equipped with large carrying handle, **protected pressure gauge** :
 - Compact when folded
 - 4 stainless steel flexible feet
 - 5 tungsten carbide spikes
 - Swivel inlets: 2x 2.5" NH F or 4" NH F
- **Turret** is equipped with **large carrying handle** and **hand wheels** for elevation and rotation adjustment. Thanks to hand wheels no need to lock manually the position: locking is automatic
 - High elevation up to 85° (from 25°)
 - Rotation from 120° left to 80° right
 - Automatic draining valve



Protected pressure
gauge



Characteristics

| Model | Weight | Dimensions Length x width x height | Item number |
|------------------|-------------------|--|-------------|
| Base 2x2.5" NH F | 25.1lbs 11.4kg | 25.2" x 9.5" x 9.9" 64 x 24 x 25 cm | CPA-210-SI |
| Base 1x4" NH F | 20.6lbs 9.36kg | 21" x 7.8" x 8.7" 53 x 20 x 22cm | CPA-210-9I |
| Turret 2.5" NH M | 24.9lbs 11.3kg | 15" x 18.5" x 12.2" 38 x 47 x 31 cm | CPA-310-I5 |

Folded dimensions

L 25.6" x w. 25.6" x h. 20.5"
L65 x w. 65 x h. 52cm



Options

Tips:

- **OneFlow:** fixed flow monitor nozzle
Ref: CDA-026-SI: 350GPM @ 100 PSI
Ref: CDA-027-SI: 500GPM @ 100 PSI
Ref: CDA-028-SI: 750GPM @ 100 PSI
- **FlowMatic:** automatic monitor nozzle
Ref: CDA-020-SI: 500 GPM @ 100 psi
Ref: CDA-022-SI: 750 GPM @ 100 psi



Reduced cost of ownership:

A very robust monitor and a very light maintenance requirement due to the design and materials used.



ZF.02.314.US.1